Parts Included



Wave Suction Band

2 oz. Silicone Adhesive

Wave Suction Band sizes				
Part Number S	Size	Diamater	Width	Thickness
CD130BS S	Small	5.5"to8.5	4"	5/32"
CD130BM N	/ledium	8.5"to12"	4"	5/32"
CD130BL L	.arge	12"to15"	4"	5/32"
CD130BX E	xtra Large	15"to18"	4"	5/32"

Manufactured by



419 N. Curtis Rd., Boise, Idaho 83706 (208) 429-0026 | www.coyotedesign.com

Coyote Design

CD130BM

Medium **Wave Suction Band**

Diameter 8.5" to 12", Width 4", Thickness 5/32"

Fabrication Instructions



3-month warranty against manufacturer defects, excessive wear or breakage. Made in U.S.A.

Clean baby powder off Wave Suction Band with

rubbing alcohol before gluing band to liner.

External Prosthetic Components



Advena Ltd Pure Offices Plato Close Tachbrook Park Warwick, CV34 6WE, UK



Attaching Seal Band



With liner on patient position band in desired location.




Mark band location on distal and proximal sides of band.



3



For unconventional band position mark band in multiple locations.



Wrap the liner with electrical tape or vynal tape next to the band without over laping it.




Tape off both ends of the band.




Remove the band



Add extra tape to protect a wider area.



9



10 Put a bead of silicone adhesive around the liner about the thickness of a pencil.



11 Smooth the silicone out with a tung depressor. Makesure to saturate the material.



Check the edges for areas that need more silicone adhesive.



13 Smooth the silicone out.



Carefully place the seal band over the glued area.



Center the band with tape to the edges.